

## Characteristics



Nuclear Applications



HEPA - Included



High Filtration Efficiency Unit



Dry Recovery



ULPA Filter Available

ULPA - Optional



Safe Containment



- Nuclear Grade HEPA filtration (H14). OSHA compliant. Constructed and tested to methods consistent with ASME AG-1
- Extra external ULPA filter (U15) available
- Electric
- For dry recovery only
- Disposable containment drum assembly
- Polycarbonate recovery tank
- Removable and reusable powerhead

## Specifications

2D-9 NUC HEPA	110626B	110626C	110626D	110626E
<b>Model Name</b>	2D-9 NUC HEPA	2D-9 NUC HEPA	2D-9 NUC HEPA	2D-9 NUC HEPA
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric
<b>Tension</b>	240 V	240 V	240 V	240 V
<b>Frequency</b>	50 Hz	50 Hz	50 Hz	50 Hz
<b>Phase</b>	Single	Single	Single	Single
<b>Wattage</b>	1050 W	1050 W	1050 W	1050 W
<b>Power</b>	1 kW	1 kW	1 kW	1 kW
<b>Amperage</b>	5 A	5 A	5 A	5 A
<b>Air Flow</b>	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O
<b>Type of Power Outlet</b>	European	UK	Swiss	Chinese
<b>Suction Inlet Port</b>	38 mm	38 mm	38 mm	38 mm
<b>Cart Type</b>	None	None	None	None
<b>Filter Cleaning</b>	None	None	None	None
<b>Cord Length</b>	10.6 m	10.6 m	10.6 m	10.6 m

Please note that specifications are subject to change without notice

**Use only recommended tools & accessories**