

## Characteristics



HEPA -  
Included



High Filtration  
Efficiency Unit



Dry Recovery



Accessories  
Included



SS 430



Low Noise



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Designed for the recovery of asbestos, lead, mold, etc.
- Lightweight and portable
- Heavy duty 2-stage by-pass motor
- Equipped with a 3-stage filtration system
- For dry recovery only
- Heavy duty plastic recovery tank
- Stainless steel recovery tank available
- Ready to use - filters and tool kit included
- 4-wheel cart for easy maneuverability
- Built-in storage tray with two large 6.75" (170 mm) rear wheels and two 2.25" (60 mm) front wheels
- 50' grounded power cord available

## Specifications

AS-400 HEPA (Dry)	110765B	110765C	110765D	110765E	110766B	110766C
<b>Model Name</b>	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH STAINLESS STEEL TANK	AS-400 HEPA WITH POLY TANK	AS-400 HEPA WITH POLY TANK
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric	Electric	Electric
<b>Tension</b>	220-240 V	220-240 V	220-240 V	220-240 V	220-240 V	220-240 V
<b>Frequency</b>	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
<b>Phase</b>	Single	Single	Single	Single	Single	Single
<b>Wattage</b>	1200 W	1200 W	1200 W	1200 W	1200 W	1200 W
<b>Power</b>	1.2 kW	1.2 kW	1.2 kW	1.2 kW	1.2 kW	1.2 kW
<b>Amperage</b>	5 A	5 A	5 A	5 A	5 A	5 A
<b>Air Flow</b>	194 m <sup>3</sup> /h	194 m <sup>3</sup> /h	194 m <sup>3</sup> /h	194 m <sup>3</sup> /h	194 m <sup>3</sup> /h	194 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2504 mm H <sub>2</sub> O	2504 mm H <sub>2</sub> O	2504 mm H <sub>2</sub> O	2504 mm H <sub>2</sub> O	2504 mm H <sub>2</sub> O	2504 mm H <sub>2</sub> O
<b>Sound Level</b>	63 dB(A)	63 dB(A)	63 dB(A)	63 dB(A)	63 dB(A)	63 dB(A)
<b>Type of Power Outlet</b>	European	UK	Swiss	Chinese	European	UK
<b>Suction Inlet Port</b>	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
<b>Cart Type</b>	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
<b>Filter Cleaning</b>	None	None	None	None	None	None
<b>Dust Recovery Tank</b>	38 L	38 L	38 L	38 L	38 L	38 L
<b>Dry Recovery - Disposable Filter Bag</b>	38 L	38 L	38 L	38 L	38 L	38 L
<b>Length</b>	50 cm	50 cm	50 cm	50 cm	50 cm	50 cm
<b>Width</b>	52 cm	52 cm	52 cm	52 cm	52 cm	52 cm
<b>Height</b>	84 cm	84 cm	84 cm	84 cm	84 cm	84 cm
<b>Weight (Vacuum Only)</b>	15 kg.	15 kg.	15 kg.	15 kg.	15 kg.	15 kg.
<b>Cord Length</b>	10 m	10 m	10 m	10 m	10 m	10 m
AS-400 HEPA (Dry)	110766D	110766E				
<b>Model Name</b>	AS-400 HEPA WITH POLY TANK	AS-400 HEPA WITH POLY TANK				
<b>Type (Powerhead)</b>	Electric	Electric				
<b>Tension</b>	220-240 V	220-240 V				
<b>Frequency</b>	50/60 Hz	50/60 Hz				
<b>Phase</b>	Single	Single				
<b>Wattage</b>	1200 W	1200 W				
<b>Power</b>	1.2 kW	1.2 kW				
<b>Amperage</b>	5 A	5 A				
<b>Air Flow</b>	194 m <sup>3</sup> /h	194 m <sup>3</sup> /h				

<b>Vacuum Pressure</b>	2504 mm H <sub>2</sub> O	2504 mm H <sub>2</sub> O
<b>Sound Level</b>	63 dB(A)	63 dB(A)
<b>Type of Power Outlet</b>	Swiss	Chinese
<b>Suction Inlet Port</b>	38 mm	38 mm
<b>Cart Type</b>	Carriage Base (CB)	Carriage Base (CB)
<b>Filter Cleaning</b>	None	None
<b>Dust Recovery Tank</b>	38 L	38 L
<b>Dry Recovery - Disposable Filter Bag</b>	38 L	38 L
<b>Length</b>	50 cm	50 cm
<b>Width</b>	52 cm	52 cm
<b>Height</b>	84 cm	84 cm
<b>Weight (Vacuum Only)</b>	15 kg.	15 kg.
<b>Cord Length</b>	10 m	10 m

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



HEPA Filter - Included



AS-400 Disposable Filter Bags (Included) and Poly Liner Recovery Bags (Optional)



AS-400 HEPA (DRY) Tools and Accessories - Included



Beater Bar - Optional