## **Characteristics**







HEPA -

Efficiency Unit

- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Heavy duty 2-stage by-pass motor
- Middle ring for poly liner recovery bag. For the recovery of wet/saturated asbestos
- For wet & dry recovery
- Polyethylene recovery tank
- Silent operation
- Mounted on a Tilting Cart (TC) for easy disposal of recovered materials



## **Specifications**

2D-16 (TC) RE HEPA MR (ASBESTOS)	110571B
Model Name	2D-16 (TC) RE HEPA MR (ASBESTOS)
Type (Powerhead)	Electric
Tension	240 V
Frequency	50 Hz
Phase	Single
Wattage	1050 W
Power	1 kW
Amperage	5 A
Air Flow	189 m <sup>3</sup> /h
Vacuum Pressure	2180 mm H <sub>2</sub> 0
Sound Level	75 dB(A)
Type of Power Outlet	European
Suction Inlet Port	50 mm
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Dust Recovery Tank	56.8 L
Liquid Recovery Capacity	57 L
Length	69 cm
Width	69 cm
Height	114 cm
Weight (Vacuum Only)	39 kg.
Cord Length	10.6 m

Please note that specifications are subject to change without notice

Website: http://www.tiger-vac.eu Email: info@tiger-vac.it

## Use only recommended tools & accessories



HEPA Filter - Included



Main Cloth Filter - Included



Dralon Pre-Filter & Liquid Filter - Included



Asbestos Polyliner (6) W retaining clip (not shown) - Included



PVC Crushproof Suction Hose Assembly - Included



Conical Nozzle and Adaptor - Included

Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077)

Website: http://www.tiger-vac.eu Email: info@tiger-vac.it