

### Characteristics



ULPA - Included



Continuous  
Duty



EX Certified



SS 304



Dry Recovery



Less than 10  
ohms



- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Includes a muffler for noise reduction
- Available with a Conductive Filter Bag (CFB) or Manual Reverse Purge with Filter Tubes (MRPFT) system
- Designed to be attached to process machines and for general cleanup
- Can also be used for the recovery of tablets in the Pharmaceutical industry
- Continuous duty single phase (TEFC) explosion proof/dust ignition proof motor
- For dry recovery only
- All stainless steel Type 304 construction
- Vertical mounting for areas with space constraints
- Static dissipative poly liner and retainer clip for the easy and safe disposal of recovered materials - included
- Includes a complete static dissipative tool kit
- Motor and switch for use in the presence of conductive metal dust is available. North-America: Class II, Group E Europe: Dust Group IIIC
- Other motor performances available

# Specifications

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



Collection Filter Bag (CFB), Static Dissipative



Filter Tubes Assembly for MRPFT models - Included



CD-230 EX (MRPFT) PHARMA



CD-120V/230V Tool Kit - Included