

Characteristics



Continuous Duty



Detachable Tank




Dry Recovery



HEPA Filter Available

HEPA - Optional



ULPA Filter Available

ULPA - Optional



Pharma Applications



Cleanroom Compatible



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed to be attached to process machines and for general cleanup in the Food industry
- Can also be used for the recovery of tablets in the Pharmaceutical industry
- Continuous duty single phase or 3-phase motor mounted vertically
- Automatic Reverse Purge (ARP) with static dissipative reverse purge cartridge
- Available in a fixed or mobile unit
- For dry recovery only
- Available in stainless steel, white powder coated or stainless steel & white powder coated versions
- Vertical mounting for areas with space constraints
- 4 wheels for easy maneuverability

Specifications

CD-2600 CR (ARP) SERIES	111473B1	111474B1	111477B1	111478B1
Model Name	CD-2600 CR (ARP) - P/C & S/S	CD-2600 CR (ARP) - P/C & S/S	CD-2600 CR (ARP) - STAINLESS STEEL	CD-2600 CR (ARP) - STAINLESS STEEL
Type (Powerhead)	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes
Tension	400 V	400 V	400 V	400 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Three	Three	Three	Three
Wattage	2200 W	3700 W	2200 W	3700 W
Power	2.2 kW	3.7 kW	2.2 kW	3.7 kW
Amperage	6 A	7.4 A	6 A	7.4 A
Air Flow	330 m ³ /h	340 m ³ /h	330 m ³ /h	340 m ³ /h
Vacuum Pressure	3300 mm H ₂ O	3560 mm H ₂ O	3300 mm H ₂ O	3560 mm H ₂ O
VRV Setting	2795 mm H ₂ O	3050 mm H ₂ O	2795 mm H ₂ O	3050 mm H ₂ O
Sound Level	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
Type of Power Outlet	Not Included	Not Included	Not Included	Not Included
Suction Inlet Port	50 mm	50 mm	50 mm	50 mm
Cart Type	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Automatic Reverse Purge (ARP)	Automatic Reverse Purge (ARP)	Automatic Reverse Purge (ARP)	Automatic Reverse Purge (ARP)
Dust Recovery Tank	36 L	36 L	36 L	36 L
Length	66 cm	66 cm	66 cm	66 cm
Width	51 cm	51 cm	51 cm	51 cm
Height	191 cm	191 cm	191 cm	191 cm
Weight (Vacuum Only)	112 kg.	112 kg.	112 kg.	112 kg.
Cord Length	10 m	10 m	10 m	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



CD-2600 Next to average sized man



CD-2600 Rear View



CD-2600 with Recovery Tank removed



Conductive Aluminized Spun Bond Reverse Purge Cartridge
(shown with and without optional skirt) - Included



HEPA Filter - Optional