

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



Pharma Applications



Cleanroom Compatible



Wet and Dry Recovery



ULPA - Included




High Filtration Efficiency Unit



Activated Carbon



Accessories Included



EMI Shielded

Specifications For CWR POLY SERIES

| Name | Part Number | Tension | Frequency | Phase | Wattage | Power | Amperage | Air Flow | Vacuum Pressure | Type of Power Outlet | Dust Recovery Tank | Dry Recovery - Disposable Filter Bag |
|-------------------------|-----------------------|---------|-----------|--------|---------|-------|----------|-----------------------|--------------------------|----------------------|--------------------|--------------------------------------|
| CWR-15 (4W) POLY | 110498B | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | European | 47.3 L | 19 L |
| | Sound Level: 75 dB(A) | | | | | | | | | | | |

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

| | | | | | | | | | | | | |
|-------------------------|-----------------------|-------|-------|--------|--------|------|-----|-----------------------|--------------------------|----|--------|------|
| CWR-15 (4W) POLY | 110498C | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | UK | 47.3 L | 19 L |
| | Sound Level: 75 dB(A) | | | | | | | | | | | |

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

| | | | | | | | | | | | | |
|-------------------------|-----------------------|-------|-------|--------|--------|------|-----|-----------------------|--------------------------|-------|--------|------|
| CWR-15 (4W) POLY | 110498D | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | Swiss | 47.3 L | 19 L |
| | Sound Level: 75 dB(A) | | | | | | | | | | | |

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

| | | | | | | | | | | | | |
|-------------------------|-----------------------|-------|-------|--------|--------|------|-----|-----------------------|--------------------------|---------|--------|------|
| CWR-15 (4W) POLY | 110498E | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | Chinese | 47.3 L | 19 L |
| | Sound Level: 75 dB(A) | | | | | | | | | | | |

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

| | | | | | | | | | | | | |
|-------------------|---|-------|-------|--------|--------|------|-----|-----------------------|--------------------------|----------|--------|-------|
| CWR-8 POLY | 110499B | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | European | 24.6 L | 9.5 L |
| | Dimensions: H76 cm x W48 cm x L58 cm Weight: 18.1 kg. Sound Level: 75 dB(A) | | | | | | | | | | | |

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

| | | | | | | | | | | | | |
|-------------------|---|-------|-------|--------|--------|------|-----|-----------------------|--------------------------|----|--------|-------|
| CWR-8 POLY | 110499C | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | UK | 24.6 L | 9.5 L |
| | Dimensions: H76 cm x W48 cm x L58 cm Weight: 18.1 kg. Sound Level: 75 dB(A) | | | | | | | | | | | |

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

| | | | | | | | | | | | | |
|-------------------|---|-------|-------|--------|--------|------|-----|-----------------------|--------------------------|-------|--------|-------|
| CWR-8 POLY | 110499D | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | Swiss | 24.6 L | 9.5 L |
| | Dimensions: H76 cm x W48 cm x L58 cm Weight: 18.1 kg. Sound Level: 75 dB(A) | | | | | | | | | | | |

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

| | | | | | | | | | | | | |
|--|----------------|-------|-------|--------|--------|------|-----|-----------------------|--------------------------|---------|--------|-------|
| CWR-8 POLY | 110499E | 240 V | 50 Hz | Single | 1050 W | 1 kW | 5 A | 189 m ³ /h | 2180 mm H ₂ O | Chinese | 24.6 L | 9.5 L |
| Dimensions: H76 cm x W48 cm x L58 cm Weight: 18.1 kg. Sound Level: 75 dB(A) | | | | | | | | | | | | |
| Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary. | | | | | | | | | | | | |

Please note that specifications are subject to change without notice

Technical Sheet For CWR POLY SERIES

ULPA FILTER AND ACCESSORIES - Included

| Part # | Description |
|--------|-------------------|
| 211027 | ULPA FILTER (U15) |

FILTERS AND ACCESSORIES FOR MODEL CWR-8 POLY - Included

| Part # | Description |
|--------|-------------------------------|
| 211265 | DOUBLE CLOTH FILTER ASSEMBLY |
| 211274 | LIQUID FILTER FILTER ASSEMBLY |

FILTERS AND ACCESSORIES FOR MODEL CWR-15 POLY - Included

| Part # | Description |
|---------|--|
| 211305A | DOUBLE CLOTH FILTER ASSEMBLY WITH LACES FOR STAINLESS STEEL FILTER CAGE (CAGE SOLD SEPARATELY) |
| 212734A | STAINLESS STEEL CAGE FOR CLOTH FILTER -ELECTROPOLISHED |

DISPOSABLE FILTER BAGS FOR MODEL CWR-8 POLY - Included

| Part # | Description |
|----------|---|
| 219028-5 | SYNTHETIC RECOVERY BAGS (WHITE) FOR EMI CWR (PACKAGE OF 5) |
| 212731 | PVC PIPE CONNECTOR FOR PAPER FILTER BAG(WITH 4 CRIMPS TO FIT ELBOW) |

DISPOSABLE FILTER BAGS FOR MODEL CWR-15 POLY - Included

| Part # | Description |
|----------|--|
| 218063-5 | SYNTHETIC RECOVERY BAGS, 10" x 28", 50mm COLLAR (PACKAGE OF 5)) |
| 211845 | PVC PIPE CONNECTOR FOR PAPER FILTER BAG FOR CWR-15 POLY TANK & MRV-15 (WITH 4 CRIMPS TO FIT ELBOW) |

DRAIN HOSE FOR MODEL CWR-15 POLY - Included

| Part # | Description |
|--------|---|
| 381092 | DRAIN HOSE ASSEMBLY 0.75" x 5'(1.5m) CLEAR HOSE w/ 0.75"(19mm) PVC FEMALE CAMLOCK |

TOOLS AND ACCESSORIES - Included

| Part # | Description |
|--------|--|
| 323404 | SUCTION HOSE ASSEMBLY,1.25"(32mm)x10'(3m)CLEAR URETHANE, ITH SS CURVED HANDLE&PLASTIC FEMALE CAMLOCK |
| 323330 | EXTENSION WANDS, BOTH STRAIGHT, 1.25"(32mm) x 20.5"(52cm), STAINLESS STEEL (SET OF 2) |
| 323311 | COMBI TOOL, 1.25"(32mm) x 10.5" (27cm), BEIGE, WITH HOLE FOR BUTTON LOCK |
| 323317 | UTILITY FLOOR TOOL WITH WHEELS & WITH SQUEEGEE BLADES 1.25"(32mm) x 12"(30cm), BEIGE PLASTIC |
| 323321 | ROUND TOOL, WITH RUBBER BLADES, Ø1.25"(32mm) |
| 323314 | UPHOLSTERY FLAT TOOL, Ø1.25"(32mm), PVC |
| 323313 | CREVICE TOOL, 1.25"(32mm) x 9"(23cm), BEIG, PVC |
| 211701 | DEFOAMING LIQUID (BOTTLE) 909 ml(31 fl oz.)- FOR WET RECOVERY MODE ONLY |

TOOLS AND ACCESSORIES - Optional

| Part # | Description |
|--------|--|
| 323470 | FOODGRADE HOSE ASSEMBLY 1.25"(32mm)x10'(3m) FOR CWR-XX (SMOOTH INSIDE & OUT) |
| 323455 | EPDM HOSE ASSEMBLY SD* AUTOCLAVABLE 1.25" x 10' (32mm x3m) w/1.5" s/S SWIVEL CAMLOCK & CURVED HANDLE |
| 323412 | FLOOR TOOL ASSEMBLY, AUTOCLAVABLE, 1.25"(32mm) x 12"(30cm), STAINLESS STEEL w/WHITE NITRILE BLADES |
| 323413 | CREVICE TOOL, AUTOCLAVABLE, Ø1.25"(32mm)x10"(25.4cm) -STAINLESS STEEL |

NEEDLE TRAP AND ACCESSORIES - Optional

| Part # | Description |
|---------|---|
| 215500 | NEEDLE TRAP ASSEMBLY, STAINLESS STEEL, 2"(50mm) INLET X 1.25"(32mm) OUTLET, ELECTROPOLISHED |
| 500235M | TIGER-CLAW ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x4.5"(11.5cm) |
| 500231M | CONICAL NOZZLE ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x7.5"(19cm) |