

Characteristics



Cleanroom
Compatible




Wet Recovery



ULPA - Included



High Filtration
Efficiency Unit



EMI Shielded




Activated
Carbon



Corrosive
Recovery



Accessories
Included



Wear Protective
Clothing (PPE)



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed for the recovery of acids and corrosive liquids
- EMI/RFI Shielded
- Heavy duty 2-stage by-pass motor
- Available with a variety of activated carbon, including KINA 3® activated carbon for the adsorption of chloride and acid vapors (HF, HCL, etc). Other types of activated carbon are available. Carbon cartridges must be ordered separately - not included
- For liquid recovery
- Acid-resistant polyethylene, nylon and PVC
- Includes a complete tool kit.

Specifications

CWR-ARU-15 (TC) POLY MRAC	110511B
Model Name	CWR-ARU-15 (TC) POLY MRAC
Type (Powerhead)	Electric
Tension	240 V
Frequency	50 Hz
Phase	Single
Wattage	1050 W
Power	1 kW
Amperage	5 A
Air Flow	189 m ³ /h
Vacuum Pressure	2180 mm H ₂ O
Sound Level	75 dB(A)
Type of Power Outlet	European
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Liquid Recovery Capacity	47.3 L
Length	69 cm
Width	76 cm
Height	122 cm
Weight (Vacuum Only)	49 kg.
Cord Length	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



ULPA Filter - Included



Liquid Filter - Included



ARU STD Tools and Accessories - Included



Activated Carbon Cartridge - Optional