

## Characteristics



Cleanroom  
Compatible



Pharma  
Applications



ULPA - Included



Stainless  
Steel  
General



Accessories  
Included



Low Noise



Dry Recovery



High Filtration  
Efficiency Unit



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- 3-stage filtration system, includes an ULPA (U15) filter, main cloth filter, and disposable filter bags
- Designed for use in contamination controlled environments
- Thru-Flow heavy duty motor
- Low noise level - only 60 dB(A) at 6.6' (2m)
- For dry recovery only
- Available with a plastic or stainless steel recovery tank
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit.

## Specifications

CR-1 ULPA	110760B	110760BP	110760C	110760CP	110760D	110760DP
<b>Model Name</b>	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric	Electric	Electric
<b>Tension</b>	240 V	240 V	240 V	240 V	240 V	240 V
<b>Frequency</b>	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
<b>Phase</b>	Single	Single	Single	Single	Single	Single
<b>Wattage</b>	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W
<b>Power</b>	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
<b>Amperage</b>	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A
<b>Air Flow</b>	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O
<b>Sound Level</b>	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)
<b>Type of Power Outlet</b>	European	European	UK	UK	Swiss	Swiss
<b>Suction Inlet Port</b>	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
<b>Cart Type</b>	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
<b>Filter Cleaning</b>	None	None	None	None	None	None
<b>Dust Recovery Tank</b>	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L
<b>Dry Recovery - Disposable Filter Bag</b>	8 L	8 L	8 L	8 L	8 L	8 L
<b>Length</b>	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
<b>Width</b>	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
<b>Height</b>	56 cm	56 cm	56 cm	56 cm	56 cm	56 cm
<b>Weight (Vacuum Only)</b>	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.
<b>Cord Length</b>	10 m	10 m	10 m	10 m	10 m	10 m
CR-1 ULPA	110760E	110760EP	110762B	110762BP	110762C	110762CP
<b>Model Name</b>	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric	Electric	Electric
<b>Tension</b>	240 V	240 V	240 V	240 V	240 V	240 V
<b>Frequency</b>	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
<b>Phase</b>	Single	Single	Single	Single	Single	Single
<b>Wattage</b>	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W
<b>Power</b>	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
<b>Amperage</b>	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A	4.3 A
<b>Air Flow</b>	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O
<b>Sound Level</b>	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)

<b>Type of Power Outlet</b>	Chinese	Chinese	European	European	UK	UK
<b>Suction Inlet Port</b>	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
<b>Cart Type</b>	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
<b>Filter Cleaning</b>	None	None	None	None	None	None
<b>Dust Recovery Tank</b>	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L
<b>Dry Recovery - Disposable Filter Bag</b>	8 L	8 L	8 L	8 L	8 L	8 L
<b>Length</b>	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
<b>Width</b>	41 cm	41 cm	41 cm	41 cm	41 cm	41 cm
<b>Height</b>	56 cm	56 cm	56 cm	56 cm	56 cm	56 cm
<b>Weight (Vacuum Only)</b>	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.	9 kg.
<b>Cord Length</b>	10 m	10 m	10 m	10 m	10 m	10 m
<b>CR-1 ULPA</b>	<b>110762D</b>	<b>110762DP</b>	<b>110762E</b>	<b>110762EP</b>		
<b>Model Name</b>	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA	CR-1 ULPA		
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric		
<b>Tension</b>	240 V	240 V	240 V	240 V		
<b>Frequency</b>	50 Hz	50 Hz	50 Hz	50 Hz		
<b>Phase</b>	Single	Single	Single	Single		
<b>Wattage</b>	1000 W	1000 W	1000 W	1000 W		
<b>Power</b>	1 kW	1 kW	1 kW	1 kW		
<b>Amperage</b>	4.3 A	4.3 A	4.3 A	4.3 A		
<b>Air Flow</b>	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h	163 m <sup>3</sup> /h		
<b>Vacuum Pressure</b>	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O	2510 mm H <sub>2</sub> O		
<b>Sound Level</b>	60 dB(A)	60 dB(A)	60 dB(A)	60 dB(A)		
<b>Type of Power Outlet</b>	Swiss	Swiss	Chinese	Chinese		
<b>Suction Inlet Port</b>	38 mm	38 mm	38 mm	38 mm		
<b>Cart Type</b>	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)		
<b>Filter Cleaning</b>	None	None	None	None		
<b>Dust Recovery Tank</b>	15.1 L	15.1 L	15.1 L	15.1 L		
<b>Dry Recovery - Disposable Filter Bag</b>	8 L	8 L	8 L	8 L		
<b>Length</b>	41 cm	41 cm	41 cm	41 cm		
<b>Width</b>	41 cm	41 cm	41 cm	41 cm		
<b>Height</b>	56 cm	56 cm	56 cm	56 cm		
<b>Weight (Vacuum Only)</b>	9 kg.	9 kg.	9 kg.	9 kg.		

**Use only recommended tools & accessories**

ULPA Filter for CR-1 ULPA - Included



Main Cloth Filter - Included



A complete tool kit is included (Part No. 323495)



A package of 5 synthetic recovery bags is included (Part No. 212500)



CR-1 ULPA with Stainless Steel Recovery Tank



#214860 HEPA/ULPA Filter Protector/Housing Kit - Available