

### Characteristics



Continuous Duty



Detachable Tank




Dry Recovery



HEPA Filter Available

HEPA - Optional



ULPA Filter Available

ULPA - Optional



Pharma Applications



Cleanroom Compatible



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed to be attached to process machines and for general cleanup in the Food industry
- Can also be used for the recovery of tablets in the Pharmaceutical industry
- Continuous duty single phase or 3-phase motor mounted vertically
- Manual Filter Shaker (MFS) system
- Available in a fixed or mobile unit
- For dry recovery only
- Available in stainless steel, white powder coated or stainless steel & white powder coated versions
- Vertical mounting for areas with space constraints
- 4 wheels for easy maneuverability

# Specifications

CD-2600 CR (MFS) SERIES	111308B1	111319B1	111464B1	111468B1
<b>Model Name</b>	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - STAINLESS STEEL	CD-2600 CR (MFS) - STAINLESS STEEL
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric
<b>TEFC Motor</b>	Yes	Yes	Yes	Yes
<b>Tension</b>	400 V	400 V	400 V	400 V
<b>Frequency</b>	50 Hz	50 Hz	50 Hz	50 Hz
<b>Phase</b>	Three	Three	Three	Three
<b>Wattage</b>	2200 W	3700 W	2200 W	3700 W
<b>Power</b>	2.2 kW	3.7 kW	2.2 kW	3.7 kW
<b>Amperage</b>	6 A	7.4 A	6 A	7.4 A
<b>Air Flow</b>	330 m <sup>3</sup> /h	340 m <sup>3</sup> /h	330 m <sup>3</sup> /h	340 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	3300 mm H <sub>2</sub> O	3560 mm H <sub>2</sub> O	3300 mm H <sub>2</sub> O	3560 mm H <sub>2</sub> O
<b>VRV Setting</b>	2795 mm H <sub>2</sub> O	3050 mm H <sub>2</sub> O	2795 mm H <sub>2</sub> O	3050 mm H <sub>2</sub> O
<b>Sound Level</b>	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
<b>Type of Power Outlet</b>	Not Included	Not Included	Not Included	Not Included
<b>Suction Inlet Port</b>	50 mm	50 mm	50 mm	50 mm
<b>Cart Type</b>	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
<b>Dust Recovery Tank</b>	36 L	36 L	36 L	36 L
<b>Length</b>	66 cm	66 cm	66 cm	66 cm
<b>Width</b>	51 cm	51 cm	51 cm	51 cm
<b>Height</b>	191 cm	191 cm	191 cm	191 cm
<b>Weight (Vacuum Only)</b>	112 kg.	112 kg.	112 kg.	112 kg.
<b>Cord Length</b>	10 m	10 m	10 m	10 m

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



CD-2600 Next to average sized man



CD-2600 Rear View



CD-2600 with Recovery Tank removed



HEPA Filter - Optional

