

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



ATEX 3rd Party Certified
CE 0081 II 2GD
Ex d IIB T4 Gb
Ex tb IIIC T135°C Db IP65
LCIE 03 ATEX 6295



HEPA - Included



Continuous Duty



EX Certified



SS 304



Dry Recovery



Less than 10 ohms

CD EX Series **IECEX** 3rd Party Certified
Ex d IIB T4 Gb
Ex t IIIC T135°C Db IP65
IECEX LCI 10.0040 X
Certified for providing an Equipment
Protection Level of EPL Db and EPL Gb



GUARANTEED for the Safe Recovery
of Combustible/Conductive Dusts

ESD Safe Vacuum Systems for Hazardous
Locations are designed to prevent ignition
hazards.

We use metal parts or Static Dissipative
Powder Coating to prevent Electrostatic
Discharge (ESD)

Specifications For CD-230V EX MRPFT HEPA

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
CD-230V EX MRPFT HEPA	112174B3	230 V	50 Hz	Single	1500 W	1.5 kW	12.3 A	212 m ³ /h	2540 mm H ₂ O	Not Included	50 L
		Dimensions: H151 cm x W48 cm x L64 cm Weight: 97 kg.									

Please note that specifications are subject to change without notice

Technical Sheet For CD-230V EX MRPFT HEPA

HEPA FILTER AND ACCESSORIES - Included

Part #	Description
211027B	HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)

FILTER TUBES ASSEMBLY - Included

Part #	Description
219150	SD* EPITROPIC POLYESTER w/PTFE FINGERS FILTER, ASSEMBLY
219154	CLOTH FINGERS FILTER, SD* EPITROPIC POLYESTER w/PTFE

TOOLS AND ACCESSORIES - Included

Part #	Description
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381364	DOUBLE BEND WAND ASSEMBLY (2pc) 1.5"(38mm) x 54"(137cm), STAINLESS STEEL w/ALUMINUM TOOL COUPLING
381236	UNIVERSAL TOOL SD* w/CONDUCTIVE BRUSH STRIPS, RUBBER BLADES, BRASS AXLE & WHEELS, 1.5" x18",ALUMINUM
381372D	CREVICE TOOL, 1.5"(38mm) x 11"(28cm), STAINLESS STEEL, FOR USE WITH HOSE CUFF WITH RING
381185A	DUSTING BRUSH, SD*, 5"(12.5cm), ALUMINUM w/STAINLESS STEEL COUPLING #381147, w/CONDUCTIVE BRISTLES

383461D	CONICAL NOZZLE ASSEMBLY(STRAIGHT)7.5"(19cm)CONDUCTVE RUBBER FOR HOSE CUFF W/RING (383461M+381147D)
211065B	MULTIMETER