

Characteristics



Cleanroom Compatible



Pharma Applications



ULPA - Included




Dry Recovery



High Filtration Efficiency Unit



Accessories Included



EMI Shielded



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- EMI/RFI Shielded
- 4-stage filtration system includes an ULPA Filter (U15), double cloth filter, and disposable filter bags. An internal OSHA compliant HEPA filter (H14) is available as a 5th stage of filtration
- Designed for use in contamination controlled environments
- Thru-Flow heavy duty motor
- For dry recovery only
- Polyethylene recovery tank with chrome plated motor head
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit.

Specifications

CR-4D	110135B	110135C	110135D	110135E	110136B	110136C
Model Name	CR-4D WITHOUT EMI FILTER	CR-4D WITHOUT EMI FILTER	CR-4D WITHOUT EMI FILTER	CR-4D WITHOUT EMI FILTER	CR-4D WITH EMI FILTER	CR-4D WITH EMI FILTER
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
Tension	240 V	240 V	240 V	240 V	240 V	240 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Single	Single	Single	Single	Single	Single
Wattage	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W
Power	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
Amperage	4.6 A	4.6 A	4.6 A	4.6 A	4.6 A	4.6 A
Air Flow	204 m ³ /h	204 m ³ /h	204 m ³ /h	204 m ³ /h	204 m ³ /h	204 m ³ /h
Vacuum Pressure	2410 mm H ₂ O	2410 mm H ₂ O	2410 mm H ₂ O	2410 mm H ₂ O	2410 mm H ₂ O	2410 mm H ₂ O
Type of Power Outlet	European	UK	Swiss	Chinese	European	UK
Suction Inlet Port	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None	None	None	None	None
Dust Recovery Tank	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L	15.1 L
Dry Recovery - Disposable Filter Bag	9.5 L	9.5 L	9.5 L	9.5 L	9.5 L	9.5 L
Length	43 cm	43 cm	43 cm	43 cm	38 cm	38 cm
Width	38 cm	38 cm	38 cm	38 cm	38 cm	38 cm
Height	71 cm	71 cm	71 cm	71 cm	76 cm	76 cm
Weight (Vacuum Only)	14.5 kg.	14.5 kg.	14.5 kg.	14.5 kg.	15 kg.	15 kg.
Cord Length	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m
CR-4D	110136D	110136E				
Model Name	CR-4D WITH EMI FILTER	CR-4D WITH EMI FILTER				
Type (Powerhead)	Electric	Electric				
Tension	240 V	240 V				
Frequency	50 Hz	50 Hz				
Phase	Single	Single				
Wattage	1000 W	1000 W				
Power	1 kW	1 kW				
Amperage	4.6 A	4.6 A				
Air Flow	204 m ³ /h	204 m ³ /h				
Vacuum Pressure	2410 mm H ₂ O	2410 mm H ₂ O				
Type of Power Outlet	Swiss	Chinese				

Suction Inlet Port	38 mm	38 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None
Dust Recovery Tank	15.1 L	15.1 L
Dry Recovery - Disposable Filter Bag	9.5 L	9.5 L
Length	38 cm	38 cm
Width	38 cm	38 cm
Height	76 cm	76 cm
Weight (Vacuum Only)	15 kg.	15 kg.
Cord Length	10.6 m	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



CR-4D Tools and Accessories with Disposable Filter Bag - Included



ULPA Filter - Included



HEPA Filter - Optional



Stainless steel holding bracket - Optional