

### European Headquarters

Tiger-Vac Europa S.R.L.  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

Tiger-Vac International Inc.  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



EMI Shielded

## Specifiche per CWR MRAC SERIES

Name	Teil Nummer	Spannung	Frequenz	Phase	Leistung	Leistung	Stromstärke	Luftstrom	Saugdruck	Typ des Leistungsausgangs	Fassungsvermögen des tanks (trocken)	fassungsvermögen des Sammelbeutel (trocken)
CWR-10 (4W) MRAC	110520B	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	European	28.4 L	19 L
	Abmessungen: H113 cm x W46 cm x L61 cm    Gewicht: 44 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-10 (4W) MRAC	110520C	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	UK	28.4 L	19 L
	Abmessungen: H113 cm x W46 cm x L61 cm    Gewicht: 44 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-10 (4W) MRAC	110520D	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	Swiss	28.4 L	19 L
	Abmessungen: H113 cm x W46 cm x L61 cm    Gewicht: 44 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-10 (4W) MRAC	110520E	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	Chinese	28.4 L	19 L
	Abmessungen: H113 cm x W46 cm x L61 cm    Gewicht: 44 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-15 (4W) MRAC	110524B	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	European	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-15 (4W) MRAC	110524C	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	UK	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-15 (4W) MRAC	110524D	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	Swiss	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												

<b>CWR-15 (4W) MRAC</b>	<b>110524E</b>	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	Chinese	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
<b>CWR-15 (4W) POLY MRAC</b>	<b>110528B</b>	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	European	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
<b>CWR-15 (4W) POLY MRAC</b>	<b>110528C</b>	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	UK	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
<b>CWR-15 (4W) POLY MRAC</b>	<b>110528D</b>	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	Swiss	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
<b>CWR-15 (4W) POLY MRAC</b>	<b>110528E</b>	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m <sup>3</sup> /h	2180 mm H <sub>2</sub> O	Chinese	47.3 L	19 L
	Abmessungen: H122 cm x W46 cm x L61 cm    Gewicht: 45 kg.    Geräuschpegel: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												

Bitte beachten Sie, dass die Spezifikationen ohne vorherige Ankündigung geändert werden können

## Dati tecnici per CWR MRAC SERIES

ULPA-FILTER UND ZUBEHÖR - Included	
Artikelnummer	Beschreibung
211027	ULPA FILTER (U15)
HEPA-FILTER - INTERN - ZUR VERWENDUNG MIT MITTELRING - Optional	
Artikelnummer	Beschreibung
211027B	HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)
FILTER UND ZUBEHÖR - Included	
Artikelnummer	Beschreibung
211305	DOUBLE CLOTH FILTER ASSEMBLY
211394A	LIQUID FILTER ASSEMBLY WITH STAINLESS STEEL RING
EINWEG-FILTERBEUTEL FÜR MODELL CWR-10 (4W) MRAC - Included	
Artikelnummer	Beschreibung
219028-5	SYNTHETIC RECOVERY BAGS (WHITE) FOR EMI CWR (PACKAGE OF 5)
211840	PVC PIPE CONNECTOR FOR PAPER FILTER BAG -STAINLESS STEEL TANK
EINWEG-FILTERBEUTEL FÜR MODELL CWR-15 (4W) MRAC - Included	
Artikelnummer	Beschreibung
218063-5	SYNTHETIC RECOVERY BAGS, 10" x 28", 50mm COLLAR (PACKAGE OF 5))
211841	PVC PIPE CONNECTOR FOR PAPER FILTER BAG -STAINLESS STEEL TANK
EINWEG-FILTERBEUTEL FÜR MODELL CWR-15 (4W) POLY MRAC - Included	
Artikelnummer	Beschreibung
218063-5	SYNTHETIC RECOVERY BAGS, 10" x 28", 50mm COLLAR (PACKAGE OF 5))
211282	PVC PIPE CONNECTOR FOR PAPER FILTER BAG
AKTIVKOHLEPATRONE - Optional	
Artikelnummer	Beschreibung

212200B	CARBON CARTRIDGE ASSEMBLY WITH 3mm CARBON (REGULAR)
212200C	CARBON CARTRIDGE ASSEMBLY WITH 3mm MERSORB ACTIVATED CARBON (FOR MERCURY VAPORS)
212200K	CARBON CARTRIDGE ASSEMBLY WITH 3mm KOGC3/KINA3 CARBON (FOR CHLORIDE VAPORS)
212200L	CARBON CARTRIDGE ASSEMBLY WITH 3mm A-3 CARBON (FOR ARSINE AND PHOSPHINE VAPORS)

#### ENTWÄSSERUNGSSCHLAUCH FÜR MODELL CWR-10/15 (4W) MRAC - Included

Artikelnummer	Beschreibung
381093	DRAIN HOSE ASSEMBLY 0.75"(19mm)x5'(1.5m) CLEAR HOSE WITH 0.75"(19mm) STAINLESS STEEL FEMALE CAMLOCK

#### ENTWÄSSERUNGSSCHLAUCH FÜR MODELL CWR-15 (4W) POLY MRAC - Included

Artikelnummer	Beschreibung
381092	DRAIN HOSE ASSEMBLY 0.75" x 5'(1.5m) CLEAR HOSE w/ 0.75"(19mm) PVC FEMALE CAMLOCK

#### WERKZEUGE UND ZUBEHÖR FÜR MODELLE CWR-10/15 (4W) MRAC - Included

Artikelnummer	Beschreibung
323403	CLEAR URETHANE HOSE ASMBLY 1.25"(32mm)x10'(3m), w/1.5" S/S FEMALE CAMLOCK, WITH S/S CURVED HANDLE
323330	EXTENSION WANDS, BOTH STRAIGHT, 1.25"(32mm) x 20.5"(52cm), STAINLESS STEEL (SET OF 2)
323311	COMBI TOOL, 1.25"(32mm) x 10.5" (27cm), BEIGE, WITH HOLE FOR BUTTON LOCK
323317	UTILITY FLOOR TOOL WITH WHEELS & WITH SQUEEGEE BLADES 1.25"(32mm) x 12"(30cm), BEIGE PLASTIC
323321	ROUND TOOL, WITH RUBBER BLADES, Ø1.25"(32mm)
323314	UPHOLSTERY FLAT TOOL, Ø1.25"(32mm), PVC
323313	CREVICE TOOL, 1.25"(32mm) x 9"(23cm), BEIG, PVC
211701	DEFOAMING LIQUID (BOTTLE) 909 ml(31 fl oz.)- FOR WET RECOVERY MODE ONLY
211065	GROUND CONTINUITY TESTER

#### WERKZEUGE UND ZUBEHÖR FÜR DAS MODELL CWR-15 (4W) POLY MRAC - Included

Artikelnummer	Beschreibung
323404	SUCTION HOSE ASSEMBLY, 1.25"(32mm)x10'(3m) CLEAR URETHANE, ITH SS CURVED HANDLE&PLASTIC FEMALE CAMLOCK
323330	EXTENSION WANDS, BOTH STRAIGHT, 1.25"(32mm) x 20.5"(52cm), STAINLESS STEEL (SET OF 2)
323311	COMBI TOOL, 1.25"(32mm) x 10.5" (27cm), BEIGE, WITH HOLE FOR BUTTON LOCK
323317	UTILITY FLOOR TOOL WITH WHEELS & WITH SQUEEGEE BLADES 1.25"(32mm) x 12"(30cm), BEIGE PLASTIC
323321	ROUND TOOL, WITH RUBBER BLADES, Ø1.25"(32mm)
323314	UPHOLSTERY FLAT TOOL, Ø1.25"(32mm), PVC
323313	CREVICE TOOL, 1.25"(32mm) x 9"(23cm), BEIG, PVC
211701	DEFOAMING LIQUID (BOTTLE) 909 ml(31 fl oz.)- FOR WET RECOVERY MODE ONLY
211065	GROUND CONTINUITY TESTER

#### NADELFÄNGER UND ZUBEHÖR - Optional

Artikelnummer	Beschreibung
215500	NEEDLE TRAP ASSEMBLY, STAINLESS STEEL, 2"(50mm) INLET X 1.25"(32mm) OUTLET, ELECTROPOLISHED
500235M	TIGER-CLAW ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x4.5"(11.5cm)
500231M	CONICAL NOZZLE ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x7.5"(19cm)