

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com




CE EX II 3D
Ex h t c III C T200°C (T85°C for BLS D version)
Dc IP6X
LCIE 19 ATEX 1001 X



IECEx 3rd Party Certified
Ex h t c III C T200°C (T85°C for BLS D version)
Dc IP6X
IECEx LCIE 15.0048



EX Certified



Less than 10 ohms



HEPA - Included



High Filtration Efficiency Unit




Coalescing Filter Element




Dry Recovery



SS 304



Wet Mix - Water



Wet Mix - Oil



SD Accessories - Included



3D Printing



Brushless Motor Available

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

Specifications For C-10 EX (IT-40L) DT (CFE) HEPA W/3D TOOL KIT

| Name | Part Number | Tension | Frequency | Phase | Wattage | Power | Amperage | Air Flow | Vacuum Pressure | Type of Power Outlet |
|--|--|-----------|-----------|--------|---------|--------|----------|-----------------------|--------------------------|----------------------|
| C-10 EX (IT-40L) DT (CFE) HEPA W/3D TOOL KIT | 113179B-3D | 220-240 V | 50/60 Hz | Single | 1200 W | 1.2 kW | 5 A | 194 m ³ /h | 2504 mm H ₂ O | Not Included |
| | Dimensions: H137 cm x W56 cm x L66 cm Weight: 42 kg. Sound Level: 72 dB(A) | | | | | | | | | |
| C-10 EX (IT-40L) DT (CFE) HEPA BLS D W/3D TOOL KIT | 113179B-BL3D | 220-240 V | 50/60 Hz | Single | 1100 W | 1.1 kW | 8 A | 215 m ³ /h | 2250 mm H ₂ O | Not Included |
| | Dimensions: H137 cm x W56 cm x L66 cm Weight: 42 kg. Sound Level: 72 dB(A) | | | | | | | | | |
| Description: With Brushless Motor | | | | | | | | | | |

Please note that specifications are subject to change without notice

Technical Sheet For C-10 EX (IT-40L) DT (CFE) HEPA W/3D TOOL KIT

| HEPA FILTERS - Included | |
|--------------------------------------|--|
| Part # | Description |
| 215372 | HEPA FILTER WITH GASKETS ON BOTH SIDES, 99.99% ON 0.3 MICRON, 11.522" OD x 9.066" ID x 2" HIGH |
| 211854 | HEPA FILTER (H14) WITH GASKET, 2"(50mm) HIGH |
| COALESCING FILTER ELEMENT - Included | |
| Part # | Description |
| 215792A-HEPA | REPLACEMENT COALESCING FILTER ELEMENT, HEPA GRADE, 4.75" HIGH, w/NITRILE GASKET #219259-04 |
| MIST ARESTOR PACK - Included | |
| Part # | Description |
| 218282 | MIST ARRESTOR SCREENS, MADE OF ALUMINUM MESH, FOR IT-40L (SET OF 6 SCREENS) |

| | |
|--------|--|
| 218284 | MIST ARRESTOR PACK ASSEMBLY (ALUMINUM SCREENS WITH STAINLESS STEEL MESH) |
|--------|--|

| | |
|---|--|
| CONDUCTIVE RECOVERY BAG - Included | |
|---|--|

| Part # | Description |
|---------|---|
| 219992A | CONDUCTIVE RECOVERY BAG FOR IT-40L MINI ENHANCED |
| 219992 | CONDUCTIVE RECOVERY BAG FOR IT-40L MINI ENHANCED (PACKAGE OF 3) |

| | |
|--|--|
| DEPRESSOR CAGE FOR CONDUCTIVE RECOVERY BAG - Optional | |
|--|--|

| Part # | Description |
|--------|---|
| 228093 | DEPRESSOR CAGE FOR CONDUCTIVE WET RECOVERY BAG FOR IT-40L, MADE OF TYPE 304 STAINLESS STEEL |

| | |
|---|--|
| TOOLS AND ACCESSORIES - Included | |
|---|--|

| Part # | Description |
|---------|---|
| 383440 | STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASSEMBLY 1.5"(38mm) x 10'(3m) FOR 1.5" CAMLOCK INTAKE |
| 381818 | CREVICE TOOL 1.5"(38mm) x 8"(20cm) w/1.5" ALUMINUM TUBE, BLACK RUBBER, CONDUCTIVE & OIL RESISTANT |
| 383312A | ROUND BRUSH ASSEMBLY, ESD SAFE PLASTIC, FOR USE WITH 1.5" (38mm) HOSE |
| 383462 | CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H) |

| | |
|---|--|
| TOOLS AND ACCESSORIES - Optional | |
|---|--|

| Part # | Description |
|---------|---|
| 381477 | DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS |
| 381448A | UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES |