

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



**ATEX** 3rd Party Certified  
CE II 2GD  
Ex h IIC T6 Gb  
Ex h IIIC T85°C Db  
LCIE 03 ATEX 6310 X

IEC IECEx  
Ex h IIC T6 Gb  
Ex h IIIC T85°C Db  
IECEX LCIE 17.0076 X




**GUARANTEED** for the Safe Recovery of Combustible/Conductive Dusts

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.  
We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

CE II 1/2 GD  
External : Ex h IIC T6 Gb Ex h IIIC T85°C Db  
Internal : Ex h IIC T6 Ga Ex h IIIC T50°C Da  
-5°C ≤ Ta ≤ +37°C  
**EN 17348 DT - Combustible dust collection**



EX Certified



Less than 10 ohms



Detachable Tank



HEPA - Included



High Filtration Efficiency Unit



Dry Recovery



SS 304



SD Accessories - Included



Cleanroom Compatible



Pharma Applications

## Specifications For SS-35 (DT) RE HEPA MFS

Name	Part Number	Air Flow	Vacuum Pressure	Dust Recovery Tank
<b>SS-35 (DT) RE HEPA MFS</b>	<b>110407</b>	204 m <sup>3</sup> /h	4570 mm H <sub>2</sub> O	35 L
	Dimensions: H117 cm x W56 cm x L66 cm    Weight: 37 kg.    Sound Level: 72 dB(A)			
Description: Specifications may vary depending upon performance of the compressor.				

Please note that specifications are subject to change without notice

## Technical Sheet For SS-35 (DT) RE HEPA MFS

### HEPA FILTER AND ACCESSORIES - Included

Part #	Description
211027B	HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)

### FILTERS AND ACCESSORIES - Included

Part #	Description
218627	MAIN FILTER ASSEMBLY, PTFE FILTER *SD*

### PRE-FILTER - Optional

Part #	Description
215179	PREFILTER ONLY WITH ELASTIC, SD*

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
212100CS	CONDUCTIVE POLY LINER WITH DRAW STRING (35/38 LITRES)

212100CS-5	CONDUCTIVE POLY LINER WITH DRAW STRING (35/38 LITRES)(PACKAGE OF 5)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

**Ø1.5" (Ø38mm) EXPLOSION PROOF TOOLS & ACCESSORIES - MANDATORY FOR USE WHEN RECOVERING CONDUCTIVE, METAL & PYROTECHNIC DUST. STATIC DISSIPATIVE (LESS THAN 10 OHMS) - Included**

Part #	Description
381400B	KANAFLEX SUCTION HOSE ASMBLY SD* 1.5"(38mm) x 10'(3m) w/HOSE CUFF w/RING, FOR USE w/2" CAMLOCK INLET
211030	AIR SUPPLY HOSE ASSEMBLY SD* 0.5"(12.7mm) x 50'(15m) w/1 MALE QUICK DISC. & 1 FEMALE QUICK DISC.
211033B	FEMALE QUICK DISCONNECT Ø0.5"(12.7mm) WITH Ø0.5"(12.7mm) FEMALE THREAD (BRASS)
211095C	HEX NIPPLE -BRASS (0.5"NPT)
381364A	WAND ASSEMBLY (2pc), 1.5" X 54", S/S WITH ALUMINUM TOOL COUPLING, w/TAPER FOR USE w/HOSE CUFF w/RING
381236	UNIVERSAL TOOL SD* w/CONDUCTIVE BRUSH STRIPS, RUBBER BLADES, BRASS AXLE & WHEELS, 1.5" x18",ALUMINUM
381372D	CREVICE TOOL, 1.5"(38mm) x 11"(28cm), STAINLESS STEEL, FOR USE WITH HOSE CUFF WITH RING
381185DA	ROUND BRUSH, ALUMINUM SD*, 5"(12.5cm), WITH CONDUCTIVE BRISTLES, FOR USE w/HOSE CUFF w/RING
383462D	CONICAL NOZZLE ASSEMBLY w/CURVED TIP 10"(25cm)CONDUCTIVE RUBBER FOR HOSE CUFF&RING(383462M+381147D)
211065B	MULTIMETER

**Ø1.5" (Ø38mm) STATIC CONDUCTIVE TOOLS AND ACCESSORIES (RESISTIVITY OF 10/3 - 10/5) - Optional**

Part #	Description
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381364	DOUBLE BEND WAND ASSEMBLY (2pc) 1.5"(38mm) x 54"(137cm), STAINLESS STEEL w/ALUMINUM TOOL COUPLING
381236	UNIVERSAL TOOL SD* w/CONDUCTIVE BRUSH STRIPS, RUBBER BLADES, BRASS AXLE & WHEELS, 1.5" x18",ALUMINUM
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM
381185A	DUSTING BRUSH, SD*, 5"(12.5cm), ALUMINUM w/STAINLESS STEEL COUPLING #381147, w/CONDUCTIVE BRISTLES
383462	CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H)

**GROUNDING REEL - Optional**

Part #	Description
211191	GROUNDING REEL, 50ft (15m), STAINLESS STEEL HOUSING & CABLE, WITH AIRCRAFT GROUNDING CLAMP