

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



ATEX 1st Party Certified
CE II 3D
Ex tc IIIC T200°C Dc IP6X

IECEx 3rd Party Certified
Ex h tc IIIC T200°C (T85°C for BLSLSD version)
Dc IP6X
IECEx LCIE 15.0048



ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

CE II 1/3 D
External : Ex h tc IIIC T200°C (T85°C for BLSLSD version) Dc IP6X
Internal : Ex h IIIC T50°C Da
-5°C ≤ Ta ≤ +37°C
EN 17348 DT / LC - Combustible dust collection / Non-flammable liquids collection



Static Dissipating



HEPA - Included



High Filtration Efficiency Unit



Stainless General



SD Accessories - Included



Wet and Dry Recovery

Specifications For C-25 EX TC WET & DRY

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
C-25 EX TC WET & DRY	111778B	220-240 V	50/60 Hz	Single	1200 W	1.2 kW	5 A	194 m ³ /h	2504 mm H ₂ O	Not Included	56.8 L
	Dimensions: H124 cm x W69 cm x L76 cm Weight: 49 kg. Sound Level: 72 dB(A)										
Description: Equipped with a Universal Motor. Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											
C-25 EX TC WET & DRY BLSLSD	111778B-BLSLSD	220-240 V	50/60 Hz	Single	1100 W	1.1 kW	8 A	215 m ³ /h	2250 mm H ₂ O	Not Included	56.8 L
	Dimensions: H124 cm x W69 cm x L76 cm Weight: 49 kg. Sound Level: 72 dB(A)										
Description: With Brushless Motor											

Please note that specifications are subject to change without notice

Technical Sheet For C-25 EX TC WET & DRY

HEPA FILTERS - Included	
Part #	Description
212304B-HD	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, HEAVY DUTY CONSTRUCTION
215372	HEPA FILTER WITH GASKETS ON BOTH SIDES, 99.99% ON 0.3 MICRON, 11.522" OD x 9.066" ID x 2" HIGH
211854	HEPA FILTER (H14) WITH GASKET, 2"(50mm) HIGH

FILTERS AND ACCESSORIES - Included	
Part #	Description
211013	MAIN FILTER ASSEMBLY SD* FOR 10/15/25 GALLON EXPLOSION PROOF VACS
212008	PRE-FILTER ASSEMBLY SD* (10,15&25 GALLON)

211010	LIQUID FILTER ASSEMBLY SD* FOR 10/15/25 GAL EXP PROOF VACS
--------	--

TOOLS AND ACCESSORIES - Included	
Part #	Description
383440	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASSEMBLY 1.5"(38mm) x 10'(3m) FOR 1.5" CAMLOCK INTAKE
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381374	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH NEOPRENE SQUEEGEE BLADES
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM