Characteristics













SS 430

- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Designed for general cleaning in the Food industry
- Heavy duty 2-stage by-pass motor
- Manual Reverse Purge (MRP) with static dissipative reverse purge cartridge
- For dry recovery only
- Heavy duty powder coated body and stainless steel recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels
- Includes a complete tool kit with a clear suction hose. A variety of optional accessories are available including autoclavable and ESD safe hoses and tools

Specifications

2D-25L (DT) MRP WT SERIES	111411B	111413B
Model Name	2D-25L (DT) MRP WT NO HEPA	2D-25L (DT) MRP WT HEPA
Type (Powerhead)	Electric	Electric
Tension	230 V	230 V
Frequency	50 Hz	50 Hz
Phase	Single	Single
Wattage	1200 W	1200 W
Power	1.2 kW	1.2 kW
Amperage	5 A	5 A
Air Flow	153 m ³ /h	153 m ³ /h
Vacuum Pressure	2030 mm H ₂ 0	2030 mm H ₂ 0
Sound Level	75 dB(A)	75 dB(A)
Type of Power Outlet	European	European
Suction Inlet Port	50 mm	50 mm
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
Dust Recovery Tank	24.6 L	24.6 L
Length	58 cm	58 cm
Width	53 cm	53 cm
Height	102 cm	102 cm
Weight (Vacuum Only)	23 kg.	23 kg.
Cord Length	10.6 m	10.6 m

Please note that specifications are subject to change without notice

Website: http://www.tiger-vac.eu Email: info@tiger-vac.it

Use only recommended tools & accessories



HEPA Filter - Included



Conductive Aluminized Spun Bond Reverse Purge Cartridge (shown with and without optional skirt) - Included



Clear Polyliner Recovery Bags - Included



Ø1.5" (Ø38 mm) Tools and Accessories - Included



25L Detachable Tank