

...The name to vacuum with

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



**ATEX** 3rd Party Certified  
CE 0081 II 2GD  
Ex d IIB T4 Gb  
Ex tb IIIC T135°C Db IP65  
LCIE 03 ATEX 6295



CD EX Series **IECEX** 3rd Party Certified  
Ex d IIB T4 Gb  
Ex t IIIC T135°C Db IP65  
IECEX LCI 10.0040 X  
Certified for providing an Equipment  
Protection Level of EPL Db and EPL Gb



Continuous  
Duty



EX Certified



HEPA Filter  
Available  
HEPA -  
Optional



ULPA Filter  
Available  
ULPA -  
Optional



Detachable  
Tank



Dry Recovery



Less than 10  
ohms



**GUARANTEED** for the Safe Recovery  
of Combustible/Conductive Dusts



This model can be used to Recover  
Combustible Dusts such as Dust Groups :  
**IIIA** Combustible Flyings (lints of cotton,  
wood chips, etc.)

**IIIB** Non-Conductive Dusts (flour dust, grain  
dust, flour, sugar, starch, wood, plastic,  
carbonaceous dusts, coal, carbon black)

**IIIC** Conductive Dusts (combustible metal  
dust, aluminum, magnesium, commercial  
alloys)

**ESD Safe** Vacuum Systems for Hazardous  
Locations are designed to prevent ignition  
hazards.

We use metal parts or Static Dissipative  
Powder Coating to prevent Electrostatic  
Discharge (ESD)

## Specifications For CD-35L (DT) EX (MRP) EXTENDED CAT. 2GD Z1-21

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
<b>CD-35L (DT) EX (MRP) EXTENDED 2GD Z1-21</b>	<b>112529B1</b>	400 V	50 Hz	Three	4000 W	4 kW	8.7 A	299 m <sup>3</sup> /h	3380 mm H <sub>2</sub> O	Not Included	35 L
	Dimensions: H142 cm x W61 cm x L102 cm		Weight: 125 kg.		Sound Level: 72 dB(A)						

Please note that specifications are subject to change without notice

## Technical Sheet For CD-35L (DT) EX (MRP) EXTENDED CAT. 2GD Z1-21

### HEPA/ULPA FILTERS AND ACCESSORIES - Optional

Part #	Description
212202	HEPA FILTER, 11" HIGH w/GASKET, EFFICIENCY OF 99.995% ON 0.3 MICRON (H14)
212203	ULPA FILTER (U15), 11"(28cm)

### REVERSE PURGE FILTER CARTRIDGE - Included

Part #	Description
--------	-------------

214182A	FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD,1" PLEATS, 13 SQ.FT
---------	---

#### SAFETY FILTER FOR REVERSE PURGE FILTER CARTRIDGE - Included

Part #	Description
215393TA-SD	MAIN FILTER ASSEMBLY w/LACES, EPITROPIC POLYESTER w/PTFE, FOR MODEL ATEX 22E (CAGE SOLD SEPARATELY)
218390	WIRE CAGE FOR CLOTH FILTER, STAINLESS STEEL TYPE 304

#### SKIRT FOR REVERSE PURGE FILTER CARTRIDGE - Optional

Part #	Description
214177	SD* SKIRT FOR FILTER CARTRIDGE, 16" HIGH X 3.63" ID X 7.932" OD

#### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
212100CS	CONDUCTIVE POLY LINER WITH DRAW STRING (35/38 LITRES)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

#### TOOLS AND ACCESSORIES - Included

Part #	Description
500540	CRUSHPROOF SUCTION HOSE ASMBLY 2"(50mm) x15'(4.5m) STATIC CONDUCTIVE w/2"(50mm) FEMALE CAMLOCK (ALUM
500160	WAND ONLY, SINGLE BEND, 2"(50mm) x 48" (122cm), ALUMINUM, WITH TAPER FOR FLOOR TOOL
500161A	UNIVERSAL TOOL Ø2"(50mm)x20"(51cm)SD* NO COUPLING WITH BRASS WHEELS&CONDUCTIVE BRISTLES&RUBBER BLADE
500156B	CREVICE TOOL SD* (NO COUPLING) Ø2"(50mm)x15"(38cm) -ALUMINUM
501184A	DUSTING BRUSH ALUMINUM SD* Ø2"(50mm)x5"(12.7cm)WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT
500230	CONICAL NOZZLE RUBBER SD* ASSEMBLY Ø2"(50mm)x7.5"(19cm) WITH Ø2"(50mm)PRESSURE FIT ALUM. CONNECTOR
211065B	MULTIMETER