

Characteristics



HEPA Filter Available
HEPA - Optional



Continuous Duty



Detachable Tank



Forklift Ready



Dry Recovery



Static Dissipating




- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- For general housekeeping
- Continuous duty 3-phase motor, 10 HP to 15 HP (11 kW to 15 kW)
- To be used with a Continuous Duty Power Unit (CDPU)
- Static dissipating and conductive
- Category 3/EPL Dc, Zone 22 (Dust)
- Automatic Purge System (APS), with either 4 aluminized spun bond filter cartridges, or 4 socks. 4 fully integrated diaphragm valves
- For dry recovery only
- Heavy duty powder coated construction. Also available in all stainless steel
- Detachable recovery tank (DT) for easy disposal of recovered materials
- System is divided into 2 main components - the Filtration Recovery System (FRS) and the Continuous Duty Power Unit (CDPU)


Specifications

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



CDPU Upstream HEPA Filter drawing



CDPU Downstream HEPA Filter drawing



Air Supply Hose Assembly with Quick Disconnect Fitting - Included



HEPA Filter - Downstream - Optional



HEPA Filter - Upstream - Optional