

Characteristics



Continuous
Duty



Dry
Recovery



- Designed to capture airborne dust
- The first stage of filtration is an aluminized spun bond cartridge. Filtration efficiency of 97% at 0.3 micron
- Downstream HEPA filter with an efficiency of 99.99% at 0.3 micron - included. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility
- Low pressure, high flow rate. 600-700 CFM (1020-1190 m³/h)
- Filter cartridge pulse cleaning by compressed air (manual or with automatic timer) with a 10L compressed air tank
- Heavy duty stainless steel Type 304 construction
- Heavy duty wheels and swivel castors. 2 wheels are equipped with brakes
- Handles for ease of movement
- Easy access to filters
- Low center of gravity to prevent tipping
- Continuous duty single phase or 3-phase (TEFC)
- Different motor voltages are available
- Optional dust extraction arm available - Ø6" (150 mm)

Specifications

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Purge Filter Cartridge - Included



CD-600/TV-600 SS Purge Filter Cartridge in housing



Optional Differential Pressure Gage for SS Models (Filter Blockage Indicator) available



Wall Mount Bracket for Dust Extraction Arm - Optional