

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts




EX Certified



Stainless General



Dry Recovery



Less than 10 ohms

Specifications For PRIMARY CYCLONIC TRANSFER DRUM ADAPTOR

Name	Part Number
PRIMARY CYCLONIC TRANSFER DRUM ADAPTOR ASSEMBLY WITH Ø2" (50mm) INTAKE	216605
PRIMARY CYCLONIC TRANSFER DRUM ADAPTOR ASSEMBLY WITH Ø2.5" (62.5mm) INTAKE	216606

Please note that specifications are subject to change without notice

Technical Sheet For PRIMARY CYCLONIC TRANSFER DRUM ADAPTOR

PRIMARY CYCLONIC TRANSFER DRUM ADAPTOR WITH Ø2" (Ø50mm) INTAKE consists of the following: - Included

Part #	Description
213980C	LID ASSEMBLY WITH 2"(50mm) CAMLOCK SUCTION INTAKE & DEFLECTOR CHAMBER FOR CYCLONIC ACTION -SS 304
213547	GASKET ASSEMBLY WITH RING, FOR 55 GALLON DRUM / REVERSE PULSE
213330C	MIDDLE RING ASSEMBLY WITH TANGENTIAL CAMLOCK SUCTION INTAKE 2"(50mm) -STAINLESS STEEL 304

PRIMARY CYCLONIC TRANSFER DRUM ADAPTOR WITH Ø2.5" (Ø64mm) INTAKE consists of the following: - Included

Part #	Description
213980D	LID WITH 2.5"(64mm)CAMLOCK SUCTION INTAKE & DEFLECTOR CHAMBER FOR CYCLONIC ACTION -SS304
213547	GASKET ASSEMBLY WITH RING, FOR 55 GALLON DRUM / REVERSE PULSE
213330D	MIDDLE RING ASSEMBLY WITH TANGENTIAL CAMLOCK SUCTION INTAKE 2.5"(64mm) -STAINLESS STEEL 304

Ø2" (Ø50mm) CONNECTION HOSE ASSEMBLY - Optional

Part #	Description
500301A	KANAFLEX CONNECTION HOSE ASSEMBLY SD* Ø2"(50mm)x5'(1.5m)WITH Ø2" SS FEMALE CAMLOCK ON BOTH ENDS

Ø2.5" (Ø64mm) CONNECTION HOSE ASSEMBLY - Optional

Part #	Description
635321	KANAFLEX CONNECTION HOSE ASSEMBLY SD* Ø2.5"(64mm)x5'(1.5m) WITH Ø2.5"(64mm) SS FEMALE CAMLOCKS